



P.O. Box 567 Route 28N North Creek, NY USA 12853 Tel: 518.251.3302 Fax:518.251.2908 www.Dura-Flex.com

PRODUCT SPECIFICATION

DURA-FLEX Part Number: 22/2WS Mic. Cable

Product Description:

A (1) Twisted Pair -- Twenty Two (22) Gauge -- Bare Copper Conductor With Polyethylene Insulation, Shielded With A Bare Copper Braid, Jacketed With Rugged, Yet Highly Flexible Polyvinylchloride.

Conductor Data:

Material	Bare Copper
Gauge	22 AWG
Stranding	26 x 36

Insulation Data:

Material	Polyethylene
Nominal Wall Thickness	.016" Nominal
Diameter (conductor)	.065" Nominal

Cabling Data:

Number Of Pairs	1
Color Code	Black And White

Shield Data:

Braid	36 AWG Bare Copper Strands
Braid Coverage	76% Nominal

Jacket Data:

Material	Highly Flexible Polyvinylchloride
Color	Black
Markings	White Lettering
Nominal Wall Thickness	.035" Nominal
Diameter (OD)	.227" Nominal
Legend	DURA-FLEX MICROPHONE CABLE --- 22 AWG 1-PAIR SHIELDED RU AWM 2464 300V 80°C E167231-A --- LOW IMPEDANCE AUDIO & COMMUNICATIONS CABLE CSA AWM IA/B 80° 300V FT1 701566 (SEQUENTIAL FOOTAGE)

Ratings:

Impedance	80 Ohms
-----------	---------