



P.O. Box 567 Route 28N North Creek, NY USA 12853 Tel: 518.251.3302 Fax: 518.251.2908 www.Dura-Flex.com

PRODUCT SPECIFICATION

DURA-FLEX Part Number: 22/2WS

Product Description:

Single Pair Microphone / Intercom Cable - A One (1) Pair -- Twenty Two (22) Gauge -- Bare Copper Conductor with Polyethylene Insulation, Shielded with a Bare Copper Braid, Black Polyvinylchloride Jacket.

Conductor Data:

Material	Bare Copper
Gauge	22 AWG
Stranding	26 x 36

Insulation Data:

Material	Polyethylene
Nominal Wall Thickness	.016" Nominal
Diameter (primary)	.065" Nominal

Cabling Data:

Number of Pairs	1
Conductor Identification	Black and White

Shield Data:

Braid	36 AWG Bare Copper Strands
Braid Coverage	76% Nominal

Jacket Data:

Material	Polyvinylchloride
Color	Black
Markings	White Lettering
Nominal Wall Thickness	.035" Nominal
Diameter (OD)	.227" Nominal
Legend	DURA-FLEX MICROPHONE CABLE --- 22 AWG 1-PAIR SHIELDED RU AWM 2464 300V 80°C E167231-A --- LOW IMPEDANCE AUDIO & COMMUNICATIONS CABLE CSA AWM IA/B 80° 300V FT1 701566 (SEQUENTIAL FOOTAGE)

Product Ratings:

Wt. / M feet Nominal	30 lbs. / 1M feet (0.03 lbs. /ft.) Nominal
Temperature Rating	80°C – AWM
Voltage	300 Volts
Impedance, Nominal	88 Ohms Nominal
Capacitance, Nominal	18 pF/ft.
Flame Test Rating	CSA - FT1

Approvals:

CSA Approval	AWM Class I, Group A/B - 701566
RoHS	RoHS Compliant