



P.O. Box 567 Route 28N North Creek, NY USA 12853 Tel: 518.251.3302 Fax: 518.251.2908 www.Dura-Flex.com

PRODUCT SPECIFICATION

DURA-FLEX Part Number: 22/4WS

Product Description:

Two Pair DMX cable - A Two (2) Twisted Pair -- Twenty Two (22) Gauge -- Tinned Copper Conductor with Cellular Polyethylene Insulation, Fully Shielded with an Overall Aluminum /Polyester Foil and Tinned Copper Braid, Jacketed with Rugged, Yet Highly Flexible black Polyvinylchloride, Power Limited Circuit Cable, Type CL, AWM Style 2919.

Conductor Data:

Material	Tinned Copper
Gauge	22 AWG
Stranding	19 x 34

Insulation Data:

Material	Cellular Polyethylene
Nominal Wall Thickness	.016" Nominal
Diameter (primary)	.062" Nominal

Cabling Data:

Number of Pairs	2
Conductor Identification	1 st Pair – Black and White 2 nd Pair – Red and Green

Shield Data:

Braid	36 AWG Tinned Copper Strands
Braid Coverage	90% Nominal
Foil	Aluminum / Polyester Tape
Drain Wire	22 AWG Tinned copper Over Foil Tape

Jacket Data:

Material	Polyvinylchloride
Color	Black
Markings	White Lettering
Nominal Wall Thickness	.035" Nominal
Diameter (OD)	.290" Nominal
Legend	DURA-FLEX DMX RS-485 — 22 AWG 2-PAIR SHIELDED TYPE CL2 (UL) 75C FT4 E244628 OR CMG OR AWM 2919 LOW VOLTAGE COMPUTER CABLE — CSA AWM 1A/B80 150V FT1 701566 (SEQUENTIAL FOOTAGE)

Product Ratings:

Wt. / M feet Nominal	50 lbs. / 1M feet (0.05 lbs. /ft.) Nominal
Temperature Rating	75°C - Type CL, 80°C – AWM
Voltage	150 Volts
Impedance, Nominal	100 Ohms Nominal
Capacitance, Nominal	14 – 15 pF/ft.

Approvals:

UL Approval	Type CL, File Number E244628
CSA Approval	AWM 1A/B80 150V FT1
RoHS	RoHS Compliant