

## **Atomic Colors**

Atomic Colors is a specially designed head which fits onto the front of the Atomic 3000 DMX - allowing up to ten brightly colored strobe and blinder effects.

Physical

Length: 470 mm (18.5 in.) Width: 273 mm (10.7 in.) Height: 102 mm (4.0 in.) Weight: 2.5 kg (5.5 lbs.)

Color gel thickness: 0.075 mm (0.003 in.) - 0.125 mm (0.005 in.)

Color gel scrolling: 10 standard colors supplied, custom color gel strings can be

fabricated by customer

Control and Programming Control options: DMX DMX channels: 1 or 2

Cooling fan speed control: Onboard control panel, DMX

Gel scrolling speed, 'gel saver' mode, light-activated fan operation: Onboard control

Setting and addressing: Three-button LED control panel DMX compliance: USITT DMX512/1990

Construction Color: Black

Finish: Electrostatic powder-coated

Housing: Steel Protection rating: IP20

Installation

Location: Indoor use only, mounted on Atomic fixture

Mounting points: Fastens to Atomic fixture

Orientation: Any

Combined power and DMX data from Atomic fixture: 4-pin XLR

Electrical

DC power: 24 V (+/- 10%) DC current: 0.55 A (max.)

Power source when used with xenon tube-based Atomic 3000 DMX: MPU-02 or MPU-08 external PSU

Cooling: Forced air (4-speed fans)

Maximum ambient temperature (Ta max.): 40° C (104° F)

Minimum ambient temperature (Ta min.): 10° C (50° F)

Included Items

10-color gel string (installed): P/N 91611090

5 m power/data cable, 4-pin XLR: P/N 11821014

User manual

Accessories MPU-02 Power Supply Unit: P/N 91611084 MPU-08 Power Supply Unit: P/N 91611085

Ordering Information

Atomic Colors for Atomic 3000: P/N 91611086



