



P.O. Box 567 Route 28N North Creek, NY USA 12853 Tel: 518.251.3302 Fax:518.251.2908 www.Dura-Flex.com

PRODUCT SPECIFICATION

DURA-FLEX Part Number: 22/6WS

Product Description:

High flex industrial low voltage computer cable - 3 Twisted Pairs w/shield -- AWM Style 2919

Conductor Data:

Material 7/30 Stranded Tinned Annealed Copper
Gauge 22 AWG

Insulation Data:

Material Cellular Polyethylene
Nominal Wall Thickness .020" Nominal
Diameter (conductor) .070" Nominal

Cabling Data:

Number of Pairs 3
Color Code P1 – Black & Red
P2 – Black & White
P3 – Green & White/Green
P3 – Black & Green
Core Construction (3) Twisted Pairs
Each Pair Twisted with 2" Nominal Left Hand Direction Lay

Shield Data:

Foil Shield Overall Aluminum/Polyester Tape Shield, Foil Facing Out
Foil Coverage 100%
Drain 22 AWG 7 Strand Tinned Copper Drain over Tape Shield

Jacket Data:

Material PVC
Color Black
Markings White Lettering
Nominal Wall Thickness .035" Nominal
Diameter (OD) .320" Nominal
Legend DURA-FLEX -- E191696 22 AWG TYPE CM (UL) 75C OR AWM 2919 LOW VOLTAGE COMPUTER CABLE --- CSA CMG 75C 701566 (**SEQUENTIAL FOOTAGE**)

Product Ratings:

Temperature Max 75°C (AWM)
Wt. / M' Nominal 50 lbs. (.05 lbs. / foot)
Voltage 300 Volts (not marked)
Nominal Capacitance 12.5 pF/ft.
UL CM 75C, AWM STYLE 2919
CSA CMG 75C