


Technical Data Sheet

Features


Wash / Beam Optical Design	Pan - 540°
LED Animation Macros	Tilt - 265°
Modular Construction	Max Speed Pan- 360° (seconds)- 2.27
Fast Service Design	Max Speed Tilt- 180° (seconds)- 1.25
Electronic Cooling System Control	Full Color LCD Display W/ Battery Mode
LED Type- 440W Bright White Engine	5-Pin DMX/RDM Connector
LED Hours- 70% Luminous output, 50,000 hrs.	Ethernet Connector
Active Thermal Control	"PowerCON True1" Connector
Fan Modes- Standard / Continuous / Studio	Pan and Tilt Locks
RDM Compatible	Road Case Included
Control Options- DMX 512 / RDM / Art-Net	
DMX Channels- 32	

Optical



Fixed Color Wheel
7 + Open

- 1- Red
- 2- Blue
- 3- Green
- 4- Yellow
- 5- Orange
- 6- Purple
- 7- Dark Blue



Rotating Gobo Wheel
6 + Open

- 1- Spokes
- 2- Dots
- 3- Perfora
- 4- Monovekto
- 5- Bars
- 6- Psych

Linear - CMY / CTO

Lens Defog System

Iris

Rotating Gobo Wheel - 6 + Open

Linear Light Frost

Linear Heavy Wash

Zoom - Beam Mode - 8-45 degrees

Wash Mode - 10-50 degrees

Photometrics

Lumens*-	20,000
CRI-	>70
Color Temperature-	6500K

Gobo Dimensions \varnothing { O.D.- 30mm (1.18 in)
Image Area- 25mm (.98 in)

* Lumens as measured by Everfine 2.0 integrating sphere and PMS-80 spectrophotometer. Calibration date March 3, 2014

Electrical

Input Power Rating- AC 100V - 240V 50/60 Hz


6.2 - 2.4 Amps

Auto Switching Power Supply

Db(A)- 38

Dimensions / Physical

Fixture Dimensions




Fixture Weight	28 Kg (61 Lbs.)
Packing Gross / Shipping Weight	67.1 Kg (148 Lbs.)
Shipping Dimensions (L x W x H)	584 x 610 x 940 mm 23 x 24 x 37 in.
Min Distance to Flammable Objects	0.5m (1.64 ft.)
Min Distance to Lighted Objects	1.5m (4.9 ft.)
Operating Temperature	0 - 45° C (32 - 113° F)
Storage Temperature	-20 - 60° C (0 - 140° F)
Compliance Approvals	CE, ETL

Mounting Options-

The fixture can be truss mounted using included mounting brackets. It can also stand upright on a stable surface.

Available Fixture Colors -	Black - PN H7010029 White - By Request
----------------------------	---





Projection Chart

Zoom Range and Distance Chart

