


## Technical Data Sheet

### Features


Modular Construction	Pan - 540°
Fast Service Design	Tilt - 265°
Electronic Cooling System Control	Max Speed Pan - 360° (seconds) - 3.66
LED Type - 600W Bright White Engine	Max Speed Tilt - 252° (seconds) - 2.59
LED Hours - 70% Luminous output, 50,000 hrs.	Full Color LCD Display W/ Battery Mode
Active Thermal Control	5-Pin DMX/RDM Connector
Fan Modes - Normal / Continuous / Studio	3-Pin DMX/RDM Connector
RDM Compatible	Powercon Connector
Control Options - DMX 512/RDM	Pan and Tilt Locks
DMX Channels - 36	Integrated Yoke Arm Handles
	Road Case Included (Single)

### Optical



Fixed Color Wheel 1

- 1 - Red
- 2 - Blue
- 3 - Green
- 4 - Orange
- 5 - Purple
- 6 - Dark Blue



Replaceable Color Wheel 2

- 1 - Magenta
- 2 - Pink
- 3 - Minus Green
- 4 - CTB-1
- 5 - CTB-2
- 6 - Amber

CMY  
CTO - Linear  
Nine Motor, Rotating Framing System  
Iris  
Six Individually Replaceable Fixed Colors

Light Wash - Linear  
Heavy Wash - Linear  
Zoom - 5 to 50°

Photometrics (by Engine)	Ultra-Brite	High CRI 6500K	High CRI 3200k
Lumens*-	26,000	20,000	13,500
CRI-	>75	>90	>90
Color Temperature-	7400K	6500K	3200K
Part Number	H7010034	H7010020	H7010021

\* Lumens as measured by Everfine 2.0 integrating sphere and PMS-80 spectrophotometer. Calibration date March 3, 2014


### Electrical

Input Power Rating - AC 100V - 240V 50/60 Hz

Power Usage- 8.6 - 3.5 Amps

Auto Switching Power Supply

### Dimensions / Physical



Fixture Weight	42 Kg (92Lbs.)
Packing Gross / Shipping Weight	83.5Kg (184 Lbs.)
Shipping Dimensions (L x W x H)	762 x 559 x 1016 mm 30 x 22 x 40 in.
Min Distance to Flammable Objects	0.5m (1.64 ft.)
Min Distance to Lighted Objects	1.5m (4.9 ft.)
Operating Temperature	0 - 45° C (32 - 113° F)
Storage Temperature	-20 - 60° C (0 - 140° F)
Compliance Approvals	CE, ETL

#### Mounting Options-

The fixture can be truss mounted using included mounting brackets. It can also stand upright on a stable surface.

Available Fixture Colors -  
 Black  
 White - By Request





## Zoom Range and Distance Chart

