

# Locking Devices

## Insul-Lock Plus Devices

### 20A Connector

# HUBBELL

### Features

- Insulgrip style body design
- Accepts up to #12/3 AWG SO cable
- UL Enclosure type 4X and IP65 rated
- Disconnectable under load
- Multiple strain relief collets to accommodate wide range of cables
- Industry standard mating

### Ordering Information

<b>Description</b> Locking female cable connector, power in, screw terminals	<b>UPC</b> 783585580852	<b>Catalog Number</b> HBLFC
<b>Cord Size</b> Accepts #18/3 up to #12/3 AWG SO Cable	<b>Color</b> Black	

### Listings

UL Recognized to US and Canadian standards  
UL50E Encl. type 4X when mated to Insul-lock plus HBLMC  
or when mated to HBLMP or HBLMPD in combination with HBLMPC or HBLMPDC  
IP65 rated when mated to Insul-lock plus HBLMC  
or when mated to HBLMP or HBLMPD in combination with HBLMPC or HBLMPDC

### Specifications

Body	Thermoplastic
Contacts	Copper Alloy
Weight	0.1

### Performance

<b>Electrical</b>	
Amperage	20A
Voltage	up to 250V AC



Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

