

# SUPERSTAR 1000 LED

MODEL 1281

**A BRIGHT, POWERFUL LED FOLLOWSPOT!**



Beam Angle 5°-14°

Local and Remote DMX Dimming

## TAKING LED TECHNOLOGY TO THE NEXT LEVEL

Lycian advanced technology pushes the LED envelope to a new level. Now green technology and brilliant output meet in the Superstar 1000 LED, model 1281. Clean, crisp output easily shaped with Lycian's top mounted, intuitive controls brings tremendous versatility to this groundbreaking followspot. Enjoy a followspot bright enough to take the place of moderate powered arc units while being environmentally conscious.

### FEATURES

1000 WATT LED

Internal Electronic Power Supply

Variable Focal Optics

Mechanical Dimmer & Nichrome Iris

Fine Focus Mechanism

Includes 4 Legged Folding Base with  
Casters & Leveling Jacks

Internal 6 color Boomerang

Quiet Fan Cooling





# SUPERSTAR 1000 LED MODEL 1281

## Architects & Engineers Specifications

The luminaire is a 1000 watt LED followspot. The spot diameter is controlled by a top mounted lever which opens and closes a nichrome steel iris. The unit also includes a top mounted fader lever and an internally mounted self-cancelling color boomerang. A 1000 watt LED is housed in the rear of the head. Optical quality lenses complete the optical system. The electronic power supply is integrated into the followspot head. A 12 foot bare ended power cord is included. The followspot ships with a steel 4 legged folding base and includes locking casters and leveling jacks. Units are cooled by quiet low volume fans. The housing is constructed of extruded aluminum and cold rolled steel powder coated in black and brown. The Lycian Superstar 1000 LED Model 1281 will be specified. Only fixtures manufactured in the USA are acceptable.

## SUPERSTAR 1000 LED PHOTOMETRICS

Distance Feet	100	125	150	200
Meters	30.5	38	45.7	61
Spot Dia. Feet	8.9	11.1	13.3	18.9
Meters	3.1	3.9	4.7	6.2
Flood Dia. Feet	24.5	30.6	36.7	48.9
Meters	7.5	9.3	11.2	14.9
Spot FC	338	216	150	85
Spot Lux	3660	2580	1610	915
Flood FC	119	76	53	30
Flood Lux	1290	818	570	323

**Beam Angle 5°- 14°**

Superstar 1000 LED Dimensions	Electrical Compatability	Order Code
Head Length      57-1/2" (146cm)	100-240V, 50 & 60 Hz	<b>1281</b>
Max. Width w/ controls    17" (43cm)		Ships with head, power cord, yoke, 4 legged folding base with casters and leveling jacks
Head Depth      18-1/4" (46.4cm)		



1315/4 Base

